

**ZT3500**



**Bobcat®**

*One Tough Animal.*

**YOUR TURF.  
YOUR  
TERMS.**

**BRING TOUGH TO TURF**

# COMMERCIAL-GRADE DURABILITY AND PERFORMANCE

Convenient maintenance and all-day mowing comfort make the ZT3500 the perfect machine for anyone ready to take on the toughest turf.



## ZT3500

MODEL NUMBER	9993501	9993502	9993503
<b>ENGINE</b>			
Model	Kaw FX651V	Kaw FX691V	Kaw FX730V
Displacement		44.3 cu. in. (726 cc)	
Fuel Capacity		7.8 gal. (29.5 L)	
Air Filter		Dual-Stage Canister	
<b>ELECTRICAL</b>			
Charging System		15 amp	
Clutch		125 lbf. (556 N)	
<b>DECK</b>			
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts		
Width	48.0 in. (1219 mm)	52.0 in. (1320 mm)	61.0 in. (1549 mm)
Adjustable Anti-Scalp Rollers	3	3	7
Cutting Height		1.5-4.8 in. (38-121 mm)	
Blade Tip Speed	17,365 fpm @ 3550 Engine rpm	18,142 fpm @ 3550 Engine rpm	18,809 fpm @ 3550 Engine rpm
Discharge Chute		Flexible Molded Polymer	
<b>FRAME</b>			
Front & Rear	Welded, 7-gauge Steel; 1.5 x 2.5 in. Steel Tubing		
Machine Length		76.0 in. (1930 mm)	79.0 in. (2006 mm)
Machine Weight	773 wet lb.	789 wet lb.	832 wet lb.
<b>TRANSMISSION</b>			
Type	HG ZT-3400 Hydrostatic Transaxles		
Pump Displacement		0.7 cu. in. (12 cc)	
Oil Capacity		1.0 gal. (4 qt)	
Forward Speed		0-10.0 mph (0-16.0 km/hr.)	
Reverse Speed (mph)		0-3.5 mph (0-5.6 km/hr.)	
<b>WHEELS</b>			
Drive Wheel Size		23 x 10.5-12	
Front Caster Wheel Size		13 x 6.5-6	
Caster Arm Attachment		Welded to Frame	
<b>SEAT</b>			
Description	High-Back, Full-Mechanical Suspension Seat		
Fore-Aft Adjustment	Seat Slide Lever		

**1000**  
HOURS

**BUMPER TO BUMPER**

**WARRANTY**





# YOU ARE ONE TOUGH ANIMAL.®

Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2020 Bobcat Company. All rights reserved.



B-2000 (08/20)

**Bobcat Company**  
250 East Beaton Drive • West Fargo, ND 58078

[Bobcat.com](http://Bobcat.com)



**Bobcat®**

***One Tough Animal.***