



Bobcat®

MORE VERSATILITY IN YOUR REACH: THE NEW TL519 TELEHANDLER

The Bobcat® TL519 telehandler is compact in size, but it brings outsized productivity to the job. With 5,500 pounds of lift capacity and more than 19 feet of lift height, this powerful telehandler takes strong capability to all kinds of tight situations.



Its 72.1-inch width, four steering modes, and two-stage, low-profile boom change the game in places other machines won't fit. Tackle tricky material handling between buildings and obstacles or take advantage of a wide array of Bobcat attachments for maximum versatility.

Thanks to the standard Power Bob-Tach® attachment mounting system, you can effortlessly change attachments and vastly increase the utilization of your machine.

SPECIFICATIONS



MODEL	TL519
Performance	
Operating Weight	9898 lb. (4490 kg)
Max. Rated Capacity	5512 lb. (2500 kg)
Max. Rated Capacity at Full Height	3968 lb. (1800 kg)
Max. Rated Capacity at Full Reach	1807 lb. (820 kg)
Auxiliary Hydraulic Flow	21.1 gpm (80 L/min.)
Hydraulic Pressure	3626 psi (250 bar)
Lift Height	232.7 in. (5910 mm)
Max. Reach	134.3 in. (3410 mm)
Reach at Max. Height (24" load center)	134.3 in. (3410 mm)
Bucket Dump Height	153.5 in. (3900 mm)
Reach at Dump Height	15.5 in. (393 mm)
Bucket Dump Angle Full Height	48°
Max. Travel Speed	
Low	4.3 mph (6.9 km/hr.)
High	17 mph (27.3 km/hr.)
Dimensions	
Tires	12 x 16.5
Length Fork Face to Rear	157 in. (3989 mm)
Length Front Tire to Rear	135.5 in. (3442 mm)
Wheelbase	92.9 in. (2360 mm)
Ground Clearance	9.8 in. (250 mm)
Cab Height	76 in. (1930 mm)
Cab Height With Beacon	82.1 in. (2085 mm)
Width	72.1 in. (1832 mm)
Inside Turning Clearance	45.9 in. (1165 mm)
Fork Turning Clearance	168.1 in. (4271 mm)
Engine	
Make/Model	Bobcat D24 Turbocharged (T4)
Fuel/Cooling	Diesel/Liquid
Cylinders	4
Horsepower	74.0 hp (54.6 kW)
Rated rpm	2400 rpm
Torque @ 1600 rpm	206.5 ft.-lb. (280 Nm)
Displacement	146.0 cu. in. (2.4 L)
Fuel Tank Capacity	17.2 gal. (65.0 L)

MODEL	TL519
Operation	
Four-Wheel Drive	Std
2-Speed Hydrostatic Transmission	Std
Two Gear Range Gearbox	-
Steering Modes	Front wheel, four wheel, crab, semi-crab
Advanced Attachment Control Mode	Std
Inching Control	Std
Dynamic Braking	Std
SAPR Brakes	Std
Features	
Self Diagnostic Troubleshooting	Std
Reversible Fan	Std
Removable Beacon	Std
ROPS/FOPS Approved Cab	Std
Cab With Heat and Air Conditioning	Std
Three-Way Adjustable Suspension Seat	Std
Automatic Air Suspension Seat	-
Front LED Work Lights	Std
Rear LED Work Lights	Std
Road Lights	Std
Pin Style Rear Hitch	Std
Front-Top-Rear Window Wipers	Std
Back-Up Alarm	Std
Retractable Seat Belt	Std
Boom Angle Indicator	Std
Ride Control Boom Suspension	-
SHS (Smart Handling System)	Std
Battery Disconnect	Std
12 Volt Accessory Port	Std
Cup Holder	Std
Attachment Capabilities	
Power Bob-Tach Attachment Mounting System	Std
Bobcat TLS Hydraulic Coupler Attachment Mounting System	-
Auxiliary Hydraulics With Quick Couplers	Std
Standard Flow	21.1 gpm (80.0 L/min.)
Hydraulic Pressure	3626 psi (250 bar)
Pressure Release Block	Std
Fingertip Auxiliary Control	Std
Fingertip Boom Extension Control	Std
Attachment Control Kit (7 pin connector)	Std

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2022 Bobcat Company. All rights reserved.



B-3012 (10/22)
SS-100-1022-86617-F

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078
Bobcat.com



Bobcat®

One Tough Animal.